






REV.	SPECIFICATION	ECN NO.	APPD.



Material:
Housing: PBT, UL94V-0, Black.
Contacts: Brass, Gold Plated over Nickel 50u" or 80~120u" Tin Plated over Nickel 50u" or 80~120u" Matte Tin Plated over Nickel 50u".

Electrical Characteristics:
Current Rating: 3 AMP.
Dielectric Withstanding Voltage: AC 1000V.
Insulator Resistance: 1000MΩ min.
Contact Resistance: 20mΩ max.
Operating Temperature: -40°C~+105°C.

***RoHS Compliant**



P.C. Board Layout

2011- Series
3 Triple Row
X No. of Pin Per Row
xx G: Gold Plated
G T: Tin Plated
MT: Matte Tin Plated
00 00: G/F
10: 10u"
15: 15u"
30: 30u"
Blank: for Tin Plated and Matte Tin Plated
S S: Straight
B B: Bulk Package

Positions	Dimension		Positions	Dimension	
	A	B		A	B
02	4.83	2.54	22	55.63	53.34
03	7.37	5.08	23	58.17	55.88
04	9.91	7.62	24	60.71	58.42
05	12.45	10.16	25	63.25	60.96
06	14.99	12.70	26	65.79	63.50
07	17.53	15.24	27	68.33	66.04
08	20.07	17.78	28	70.87	68.58
09	22.61	20.32	29	73.41	71.12
10	25.15	22.86	30	75.95	73.66
11	27.69	25.40	31	78.49	76.20
12	30.23	27.94	32	81.03	78.74
13	32.77	30.48	33	83.57	81.28
14	35.31	33.02	34	86.11	83.82
15	37.85	35.56	35	88.65	86.36
16	40.39	38.10	36	91.19	88.90
17	42.93	40.64	37	93.73	91.44
18	45.47	43.18	38	96.27	93.98
19	48.01	45.72	39	98.81	96.52
20	50.55	48.26	40	101.60	99.06
21	53.09	50.80			

Standard item:
ie: 2011-3XxxG00SB(Total Length 11.6mm, Dip 3.0mm, Mate 6.1mm)
Custom item:
ie: 2011-3XxxG00S-2.5-5.9B(2011-3XxxG00S-L1-L2B)
 2.5mm Dip Length(increment of 0.1mm)
 5.9mm Mate Length(increment of 0.1mm)

Tolerances	Dwg. No.	2011D01005		Title:	
.x = ±0.30 .xx = ±0.20	Projection			2011 Series	
	Unit	mm	Scale	Pin Header 2.54mmX2.54mm	
	Drawn By	Martin 08/21'24		Triple Row Straight Solder Type	

OUPIIN
OUPIIN ELECTRONIC(KUNSHAN) CO., LTD.
P/N: 2011-3XxxG00SB
 SHEET 1/1 Ver.No. B7